



KC HiLITES

FLEX Single & Dual LED Lights



FLEX Single

FLEX Dual





FLEX SINGLE & DUAL LED LIGHTS

FEATURES

- **FLEX Single Spread Beam – #269 Two Lights & Wiring Harness**
Each Light Rated at: 10-Watt; 975 Lumens;
170 LUX @ 10 Meters; 17,000 Candela
- **FLEX Single Spot Beam – #270 Two Lights & Wiring Harness**
Each Light Rated at: 10-Watt; 975 Lumens;
250 LUX @ 10 Meters; 25,000 Candela
- **FLEX Dual Spot Beam – #271 One Light & Wiring Harness**
Rated at: 20-Watt; 1,950 Lumens;
500 LUX @ 10 Meters; 50,000 Candela
- **FLEX Dual Spread – #272 One Light & Wiring Harness**
Rated at: 20-Watt; 1,950 Lumens;
350 LUX @ 10 Meters; 35,000 Candela
- Cree XM-L2 U2 LEDs
- 5,700K Color Temperature
- 50,000 Hour LED Life
- Precision Reflector Optics
- Operates on 9 to 18 Volts
- IP68 Rated Die-Cast Aluminum Housings
- Protected Against EMI Interference

Patent Pending: Flex Power-Strip


PHOTOMETRICS



FLEX SINGLE

FLEX LED LIGHT DIMENSIONS

FLEX DUAL



KC FLEX LED SINGLE/DUAL LIGHTS

Pair Pack Part No.	Single Light Part No.	Model / Description	Beam Pattern	No. of LEDs	Watts	Amps	Volts	Lumens	Dimensions			
									A	B	C	D
269*	1269	FLEX Single LED Light	Spread	1	10	1	9-18	975	2.92"	2.0"	2.45"	2.25"
270*	1270	FLEX Single LED Light	Spot	1	10	1	9-18	975	2.92"	2.0"	2.45"	2.25"
n/a	271*	FLEX Dual LED Light	Spot	2	20	2	9-18	1,950	3.25"	2.0"	2.45"	4.25"
n/a	272*	FLEX Dual LED Light	Spread	2	20	2	9-18	1,950	3.25"	2.0"	2.45"	4.25"

* Includes Wiring Harness